

INDUSTRIAL LINE

power
and innovation

360 L
Fuel Tank
capacity

designed and created
for your needs

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

MGTP
170 SS-FI




more sustainable
and environmentally
friendly future

TRIME
Power Division

MGTP 170 SS-FI

GENSET MODEL



APPLICATIONS



Constructions



Mining operations



Events



Military applications

FEATURES

- ✓ Hard wires connection protected
- ✓ Electrical panel ComAp AMF25 mounted on board with safety cover
- ✓ Circuit breaker
- ✓ Internal exhaust gas silencer and insulated manifold
- ✓ Engine oil extraction pump and fuel decanter filter
- ✓ 12V Battery with battery switch
- ✓ Bunded tank
- ✓ Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko

KIT socket TPS03: 1x63A, 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko
125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank 800 l



easy handling & transportability

Code	IP202-170TS0
Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
Dimensions	
L x W x H (mm)	3060 x 1140 x 2200
Weight (Kg)	2100
Technical Data	
Prime Power (PRP) (kVA)	174
Prime Power (PRP) (kW)	139,2
Limited Power (LTP) (kVA)	191
Limited Power (LTP) (kW)	152,8
Rated Power Factor (cos φ)	0.8
Windings	Three phases Series Star
Rated three-phase concatenated Voltage (V)	400
Rated phase-neutral voltage (V)	230
Rated frequency (Hz)	50
Fuel Tank Capacity (l)	360
Fuel type	Diesel
Sound pressure 7 m. (dBA)	68
Fuel Consumption	
Fuel Cons. at 100% (LTP) (l/h)	42,2
Fuel Cons. at 100% (PRP) (l/h)	36,6
Fuel Cons. at 75% (PRP) (l/h)	27,5
Fuel Cons. at 50% (PRP) (l/h)	18
General Alternator data	
Alternator brand	STAMFORD
Alternator model	UCI274F
PRP Power (kVA)	180
LTP Power (kVA)	194
Winding	Three phases Series Star
Terminals Number	12
IP Protection	23
Electronic regulator	AS440
Precision	± 1 %
General Engine data	
Engine brand	FPT IVECO
Engine model	N67TM4
Cylinders	6
R.P.M.	1500
Cubic capacity	6700
Air intake	Turbo
Standard voltage (Vdc)	12
Sae	3 - 11
BMEP (kPa)	1850
Cooling	Water
Flywheel P.R.P. Power (kW)	149,7
Flywheel Stand-by Power (kW)	165
Electronic regulator	On request
Precision class	G2
Oil quantity (l)	17,2
EU Stage	Non emission certified



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.