

T-ZERO^{PRO}

POWER & INNOVATION



Kubota



1500 RPM



WATER cooled



DIESEL



SINGLE phase



SOLAR HYBRID technology



LITHIUM battery

STAGE 5
CERTIFIED

MGTP 8000/12 THS

Code **RP47-8MS12S**

Technical data

Continuous power (VA)	8000
Battery pack capacity (Wh)	11776
Capacity available DOD 80% (Wh)	9421
Voltage (V)	230
Frequency (Hz)	50

Inverter

Nominal power (VA)	8000
Q.ty	1
System voltage (V)	48
Max charging current (A)	110

Batteries

Type	LiFePO4
Q.ty	2
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	230
Cycle Life DOD 80%	> 4000

Solar Panels

Power	40
Q.ty	4
Type	Monocrystalline
Tilting	Electric
Solar charger	MPPT 150/35

Engine

Brand	Kubota
Model	D1105
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (l)	200

Alternator

Brand	Linz
Model	PRO 18S A/4
Rated output (kVA)	20
Frequency (Hz)	50
Power factor (cos φ)	0,8

Distribution Panel

Inlet Plug	1x 32A-230V
Outlet Sockets	1x 32A-230V 1x 16A-230V



Performances

Running time on batteries (h) 25% load	6,0
Running time on batteries (h) 50% load	3,0
Running time on batteries (h) 75% load	2,0
Recharge time from engine (h)	3,5

Standard Features

DSE 3110 controller	Sides forklift pockets & Central lifting hook
5" Touch monitoring display controller	Lockable control panel
Communication-centre device	Main circuit breaker & Earth leakage relay
48V/400A BMS to protect the batteries	Emergency Stop button
4G/GPS Antenna + Modem	Bunded tank
Remote telemetry & management	3-way valve for external tank
Auto recharge of the batteries	Battery switch
Automatic peak shaving mode	

Available optionals

- MC4 connectors + MPPT solar charger for external solar panels
- Mat heating system for batteries to work in cold ambients

Dimension

Length (mm)	1700
Width (mm)	1066
Height (mm)	1450
Dry weight (Kg)	920

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.