


LED TECHNOLOGY

14000 sqm
Illuminated area

ENGINE POWERED Line




Operation: **ENGINE POWERED**
fuel tank capacity 115 litres
Kubota D1105

X-RENT
6X320W 48V LED - 8,5M




X-RENT

6X320W 48V LED - 8,5M



FEATURES

- 6x320W high efficiency LED floodlight system
- Illuminated area 5400 sqm
- On/Off switches - for each pair of lamps
- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower
- Max height 8,5m
- Hydraulic lifting system
- 340° rotatable mast
- **Fully bunded tank, 110%**
- Digital control panel and fuel level indicator
- Simple, rugged machine design and layout
- Guided main coiled cable to avoid damage during tower operation
- On board level for guidance during stabilization
- Galvanized metalwork, 80 µm powder coating
- Wind stability up to 80 km/h
- **Road tow trailer**
- 4 height adjustable stabilizers
- Central lifting eye & side forklift pockets



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
		2560x1380x2500 (LxWxH)		2560x2170x8500 (LxWxH)		1100	
Floodlights	Type	Power (each)	Floodlights number	Options	Illuminated area (sqm)		
	Led	320W	6	Homologated axle & towing hitc	14000		
Mast	Lifting method	Max Height	Max Wind Speed	Rotation			
	Hydraulic	8,5 m	110 km/h	340°			
Alternator	Model	Frequency (Hz)	Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50	H	IP 23	8,5 kVA	1x16A - 240V	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota D1105*	Diesel	1500	115	1,6	71 h	68

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used